

LED SMD LINEAR LUMINAIRE

Code:
TETE4565

2 YEARS
GUARANTEE




LINKABLE
max 450W

IP67
Fast connector is included

Application

- This luminaire is suitable for outdoor installation



Technical Data

Housing Material	Polycarbonate
Optic Material	Opal Polycarbonate
Color	White
Input Voltage	230V AC
Input Frequency	50~60Hz
Total Wattage	45W
LED Type	SMD (LM80)
Lifespan	30.000 hours
Protection Class	CLASS II ☐
Ingress Protection	IP66
Mechanical Impact Degree	IK08
LED Driver	Yes (Built in)
Dimming	No
Replaceable LED / Driver	No / No
Power Cable	2*0.75mm ² (250mm)

Photometrical Data

Color Temperature	6500K
Lumen	4500Lm
Light Beam Spread	120° Symmetric
Color Rendering Index (Ra)	80

Energy Data

Energy Efficiency Label	E
Energy Consumption	45.0 kWh/1000h

The technical data of the product may differ from the listed +/- 10%



APOSTOLIDIS TRADING
Industrial area of Serres | 62100 Serres, Greece
T. +30 23210 77020-21 | F. +30 23210 77022
info@acalight.gr | www.acalight.gr

